




NEW PRODUCTS

HOKUYO

FIBER ATTACHMENT FOR PK7, PK8 AND PX7 SERIES

Specifications

Type	For condensing (Attachment with lens)		For side-on detection (Side-view)		For variable beam		
Features							
Model No.	FP1-A01		FP1-A02		FP2-A01		
Functions	Long distance detection of 1m is possible with this attachment. The unit can be used in stable operation where disturbing light, much dust or oil is present.		Attachment for through-beam type, which has projecting and receiving holes on the side. It is easily mounted where sufficient depth is not available.		Attachment which can adjust a beam to the detection position and the target diameter. Suitable for detecting fine articles.		
Applicable fiber	EP1-321	EP3-321	EP1-321	EP3-321	EP2-321	EP4-321	
Detection distance	PK7/PK8	2m	1m	30cm	8.5cm	2m	1m
	PX7	1m	50cm	12cm	4cm	1m	50cm




Type	For variable beam in limited distance	For side-on detection by reflection	Mounting bracket		
Features					
Model No.	FP2-A02	FP2-A03	FP2-A04		
Functions	Highly sensitive detection in a limited range is possible. Suitable for detection in a limited range and for mark detection.	Attachment for reflection type, which has projecting and receiving holes on its side. As like through-beam type, it can be easily mounted where sufficient depth is not available.	Attachment for the unit with fiber stretching along the side or on top of a table or machine.		
Applicable fiber	EP2-321	EP2-321	EP2-321	EP4-321	
Detection distance	PK7/PK8	2cm	6.5cm	30cm	7.5cm
	PX7	2cm	3cm	12cm	3.5cm

PHOTO SENSOR, LASER SENSOR, MICROWAVE SENSOR, COUNTER, AUTOMATIC DOOR



HOKUYO AUTOMATIC CO.,LTD.
 2-1-12 Sonezaki, Kita-ku, Osaka, Japan
 Tel(06)6362-6331 Fax(06)6365-8985
<http://www.hokuyo-aut.co.jp>
 E-mail:foreign-trade@hokuyo-aut.co.jp