



DC Contactor Types: CTT200-CTT400

Specifications

Spec	CTT200	CTT400
Coil Data		
Rated voltage	6 - 110VDC	6 - 110VDC
Pick-up voltage	66% max(Nominal voltage)	66% max(Nominal voltage)
Drop out voltage power to set	10% min(Nominal voltage)	10% min(Nominal voltage)
Coil power consumption	10 to 15(Watts)	13 to 25(Watts)
Contact data		
Max.current(A)	200A	400A
Max.contact voltage	250VDC	250VDC
Max.contact current	300A at 96VDC	600A at 96VDC
Contact closes time voltage	30ms	40ms
Ambient temperature	-40 ~ 80°C	-40 ~ 80°C
Aux. switch	DT, 5A at under 250VAC	DT, 5A at under 250VAC

Technology & Certification

- As arc can be detached with the application of the permanent magnet, switching is available up to 250VDC.
- Attachable & detachable product with easy-to-use & install
- Fashionable product manufactured in excellent design
- Auxiliary contact : 5A 24VDC(1a1b)

* Applications

Power-supply, an electric-car, a wireless remote communication equipment, a satellite station, a rectifier

Welding machine, a railway work, an unmanned transport vehicle, power transformer system. ect.



İmaj Teknik Elektrik Elektronik San. ve Tic. Ltd. Şti.

EMEYEMEZ MAH.TUTSAK SOK. NO: 16/13-14-15
KARAKOY/İSTANBUL
TURKEY

Telefon : +90 212 235 9535 / 36
Fax : +90 212 235 9537

www.imajteknik.com
www.imajteknik.com.tr